

PRODUCT DATA SHEET

For further information or assistance, contact: NCP Chlorchem Specialities Division
PO Box 150 Kempton Park 1620 • Tel: 011 921 3334 Fax: 011 976 4736



ULTRAFLOC 3750

TDS 006/R0
2024-04-02

ULTRAFLOC 3750 is a liquid, cationic aluminium chlorohydrate coagulant blend.

APPLICATION

ULTRAFLOC 3750 is a aluminium chlorohydrate coagulant designed to provide superior coagulation for clarification of raw water and effluent water. ULTRAFLOC 3750 has the advantage of having little or no effect on water pH. The product is approved by NSF/ANSI/CAN 60 for the treatment of potable water supplies at dosages up to 66 mg/l.

ULTRAFLOC 3750 is generally dosed as product with in line dilution at the dosing point.
ULTRAFLOC 3750 should not be diluted to less than 20% as a stock solution.

TYPICAL PROPERTIES

Appearance :	Clear to slightly hazy blue solution
SG (at 25°C) :	1.12-1.17
Aluminium (Al% m/m) :	5.0-5.80
Viscosity (cps at 25°C) :	100 max
pH (15% m/m at 25°C) :	3.0-4.5

TECHNICAL SERVICE

The Specialities division has a team of technical experts who will undertake all the necessary investigations and trials to ensure that you obtain the most effective treatment solutions. To ensure the best results are achieved optimum product dosage and ideal plant conditions are required.

OTHER PRODUCTS

NCP Chlorchem specialises in a wide range of products. The range includes:

POLYAMINES	FERROUS CHLORIDE
POLYDADMACS	CAUSTIC SODA LYE (NaOH)
ALUMINIUM CHLOROHYDRATE	HYDROCHLORIC ACID
ALUMINIUM CHLOROHYDRATE/POLYAMINE BLENDS	SODIUM HYPOCHLORITE
ALUMINIUM CHLOROHYDRATE/POLYDADMAC BLENDS	
FERRIC CHLORIDE	